

# EPSON LX300, EPSON LX300+.

## I. EPSON LX300+

1. (Current settings):

|  |               |
|--|---------------|
| 1) Page length for tractor                       | 12 inch       |
| 2) Skip over perforation                         | off           |
| 3) Auto tear Off                                 | off           |
| 4) Auto line feed                                | off           |
| 5) Print direction                               | Bi-D          |
| 6) Software                                      | ESC/P         |
| 7) 0 slash                                       | 0             |
| 8) High speed draft                              | On            |
| 9) I/F mode                                      | Auto          |
| 10) Auto I/F wait time                           | 10 seconds    |
| 11) Baud rate                                    | 9600BPS       |
| 12) Parity                                       | None          |
| 13) Data length                                  | 8bit          |
| 14) Parallel I/F bidirectional mode              | On            |
| 15) Packed mode                                  | Auto          |
| 16) Character table                              | PC 866        |
| 17) International character set for Italic table | Italic U.S.A. |
| 18) Manual feed wait time                        | 1.5 seconds   |
| 19) Buzzer                                       | On            |
| 20) Auto CR (IBM 2380 Plus)                      | Off           |
| 21) IBM character table                          | Table 2       |

2. :

2.1 ;

2.2 ;

2.3 “Tear off” “Load/Eject”

2.4 “Current settings”.

( .1),

( 1, 10, 17, 18 19). 11 (Baud rate) –

RS232 -22/ OE-

V(P)T ( 9600 BPS),

“Tear off”

“Font” (1- 2- ) “Pause” (3- )

“Tear off”.

:

-

-

- 1

☒ - 2

| Font | Pause |   |
|------|-------|---|
| 1    | 2     | 3   |
|      |       | Page length for tractor .                       |
|      |       | Skip over perforation .D                        |
|      |       | Auto tear Off .E                                |
|      |       | Auto line feed .F                               |
|      |       | Print direction .G                              |
|      |       | Software .H                                     |
|      |       | 0 slash .J                                      |
|      |       | High speed draft .I                             |
|      |       | I/F mode .K                                     |
|      |       | Auto I/F wait time .L                           |
|      |       | Baud rate .M                                    |
|      |       | Parity .N                                       |
|      |       | Data length .O                                  |
|      |       | Parallel I/F bidirectional mode .P              |
|      |       | Packed mode .Q                                  |
|      |       | Character table .R                              |
|      |       | International character set for Italic table .S |
|      |       | Manual feed wait time .T                        |
|      |       | Buzzer .U                                       |
|      |       | Auto CR (IBM 2380 Plus) .V                      |
|      |       | IBM character table .W                          |

, : “Character table”

LF/FF

“ 866”:

R (Character table).

:

Font Pause  
1 2 3

“Page length for tractor” .

|          |           |
|----------|-----------|
| 3 inch   | 8.5 inch  |
| 3.5 inch | 11 inch   |
| 4 inch   | 70/6 inch |
| 5.5 inch | 12 inch   |
| 6 inch   | 14 inch   |
| 7 inch   | 17 inch   |
| 8 inch   | Others    |

|      |       |   |                           |    |
|------|-------|---|---------------------------|----|
| Font | Pause |   |                           |    |
| 1    | 2     | 3 | “ Skip over perforation ” | .D |
|      |       |   | Off                       |    |
|      |       |   | On                        |    |
| Font | Pause |   |                           |    |
| 1    | 2     | 3 | “ Auto tear Off ”         | .E |
|      |       |   | Off                       |    |
|      |       |   | On                        |    |
| Font | Pause |   |                           |    |
| 1    | 2     | 3 | “ Auto line feed ”        | .F |
|      |       |   | Off                       |    |
|      |       |   | On                        |    |
| Font | Pause |   |                           |    |
| 1    | 2     | 3 | “ Print direction ”       | .G |
|      |       |   | Bi-D                      |    |
|      |       |   | Uni-D                     |    |
| Font | Pause |   |                           |    |
| 1    | 2     | 3 | “Software”                | .H |
|      |       |   | ESC/P                     |    |
|      |       |   | IBM 2380 Plus             |    |
| Font | Pause |   |                           |    |
| 1    | 2     | 3 | “0 slash ”                | .J |
|      |       |   | O                         |    |
|      |       |   | Ø                         |    |
| Font | Pause |   |                           |    |
| 1    | 2     | 3 | “ High speed draft ”      | .I |
|      |       |   | Off                       |    |
|      |       |   | On                        |    |
| Font | Pause |   |                           |    |
| 1    | 2     | 3 | “ I/F mode ”              | .K |
|      |       |   | Auto                      |    |
|      |       |   | Parallel                  |    |
|      |       |   | Serial                    |    |
| Font | Pause |   |                           |    |
| 1    | 2     | 3 | “ Auto I/F wait time”     | .L |
|      |       |   | 10 seconds                |    |
|      |       |   | 30 seconds                |    |

| Font | Pause |   |                |
|------|-------|---|----------------|
| 1    | 2     | 3 |                |
|      |       |   | “Baud rate” .M |
|      |       |   | 19200BPS       |
|      |       |   | 9600BPS        |
|      |       |   | 4800BPS        |
|      |       |   | 2400BPS        |
|      |       |   | 1200BPS        |
|      |       |   | 600BPS         |
|      |       |   | 300BPS         |

| Font | Pause |   |             |
|------|-------|---|-------------|
| 1    | 2     | 3 |             |
|      |       |   | “Parity” .N |
|      |       |   | None        |
|      |       |   | Even        |
|      |       |   | Odd         |
|      |       |   | Ignore      |

| Font | Pause |   |                  |
|------|-------|---|------------------|
| 1    | 2     | 3 |                  |
|      |       |   | “Data length” .O |
|      |       |   | 8 bit            |
|      |       |   | 7 bit            |

| Font | Pause |   |                                      |
|------|-------|---|--------------------------------------|
| 1    | 2     | 3 |                                      |
|      |       |   | “Parallel I/F bidirectional mode” .P |
|      |       |   | Off                                  |
|      |       |   | On                                   |

| Font | Pause |   |                  |
|------|-------|---|------------------|
| 1    | 2     | 3 |                  |
|      |       |   | “Packet mode” .Q |
|      |       |   | Auto             |
|      |       |   | Off              |

| Font | Pause |   |                      |
|------|-------|---|----------------------|
| 1    | 2     | 3 |                      |
|      |       |   | “Character table” .R |
|      |       |   | Italic               |
|      |       |   | PC437                |
|      |       |   | PC850                |
|      |       |   | PC437 Greek          |
|      |       |   | PC853                |
|      |       |   | PC855                |
|      |       |   | PC852                |
|      |       |   | PC857                |
|      |       |   | PC866                |
|      |       |   | PC869                |

MAZOWIA  
 Code MJK  
 ISO 8859-7  
 ISO Latin 1T  
 Bulgaria  
 PC774  
 Estonia  
 ISO 8859-2

| Font | Pause |   |   |
|------|-------|---|---|
| 1    | 2     | 3 |   |
|      |       |   | “International character set for Italic table” .S |
|      |       |   | Italic U.S.A. Italic Denmark 1                    |
|      |       |   | Italic France Italic Sweden                       |
|      |       |   | Italic Germany Italic Italy                       |
|      |       |   | Italic U.K. Italic Spain 1                        |

| Font | Pause |   |                            |
|------|-------|---|----------------------------|
| 1    | 2     | 3 |                            |
|      |       |   | “Manual feed wait time” .T |
|      |       |   | 1 second                   |
|      |       |   | 1.5 seconds                |
|      |       |   | 2 seconds                  |
|      |       |   | 3 seconds                  |

| Font | Pause |   |             |
|------|-------|---|-------------|
| 1    | 2     | 3 |             |
|      |       |   | “Buzzer” .U |
|      |       |   | Off         |
|      |       |   | On          |

| Font | Pause |   |              |
|------|-------|---|--------------|
| 1    | 2     | 3 |              |
|      |       |   | “Auto CR” .V |
|      |       |   | Off          |
|      |       |   | On           |

| Font | Pause |   |                          |
|------|-------|---|--------------------------|
| 1    | 2     | 3 |                          |
|      |       |   | “IBM character table” .W |
|      |       |   | Table 1                  |
|      |       |   | Table 2                  |

“Tear off”,  
 . . .  
 “Tear off”  
 LF/FF  
 ( ÷W) , “ haracter table”.  
 .2.4. , .1 ,

EPSON LX300

1. (Current settings):

|                          |                        |
|--------------------------|------------------------|
| 1) Character spasing     | 12 cpi                 |
| 2) Shape of zero         | 0                      |
| 3) Skip-over-perforation | Off                    |
| 4) Character table       | PC 866                 |
| 5) Auto line feed        | off                    |
| 6) Page length           | 12 inch                |
| 7) Auto tear Off         | Off                    |
| 8) Tractor               | Single                 |
| 9) Interface             | Auto selection (10sec) |
| 10) Bit rate             | 9600BPS                |
| 11) Parity               | None                   |
| 12) Data length          | 8bit                   |
| 13) ETX/ACK              | Off                    |
| 14) Software             | ESC/P                  |
| 15) Auto CR              | Off                    |

2. .1 :

2.1 ;

2.2 ;

2.3 "Font"

2.4 A ( ),

2.5 "LF/FF" "Current settings".

.1,

10 (Bit rate) – RS232

-22/ OE-V(P)T ( 9600 BPS),

"LF/FF"

"Font" (1- 2- ) "Pause" (3- )

:

-

-

-

| Font | Pause |   |                          |
|------|-------|---|--------------------------|
| 1    | 2     | 3 |                          |
|      |       |   | Character spasing .      |
|      |       |   | Shape of zero .D         |
|      |       |   | Skip-over-perforation .E |
|      |       |   | Character table .F       |
|      |       |   | Auto line feed .G        |
|      |       |   | Page length .H           |
|      |       |   | Auto tear Off .I         |
|      |       |   | Tractor .J               |
|      |       |   | Interface .K             |
|      |       |   | Bit rate .L              |
|      |       |   | Parity .M                |
|      |       |   | Data length .N           |
|      |       |   | ETX/ACK .O               |
|      |       |   | Software .P              |
|      |       |   | Auto CR .Q               |

, : "Parity", "Pause"  
 . LF/FF  
 "None": M.

:

| Font | Pause |   |                       |
|------|-------|---|-----------------------|
| 1    | 2     | 3 |                       |
|      |       |   | "Character spasing" . |
|      |       |   | 10 cpi                |
|      |       |   | 12 cpi                |

| Font | Pause |   |                    |
|------|-------|---|--------------------|
| 1    | 2     | 3 |                    |
|      |       |   | "Shape of zero" .D |
|      |       |   | 0                  |
|      |       |   | Ø                  |

| Font | Pause |   |                            |
|------|-------|---|----------------------------|
| 1    | 2     | 3 |                            |
|      |       |   | "Skip-over-perforation" .E |
|      |       |   | Off                        |
|      |       |   | On                         |

| Font | Pause |   |                   |    |
|------|-------|---|-------------------|----|
| 1    | 2     | 3 |                   |    |
|      |       |   | “Character table” | .F |
|      |       |   | Italic U.S.A.     |    |
|      |       |   | Italic France     |    |
|      |       |   | Italic Germany    |    |
|      |       |   | Italic U.K.       |    |
|      |       |   | Italic Denmark 1  |    |
|      |       |   | Italic Sweden     |    |
|      |       |   | Italic Italy      |    |
|      |       |   | Italic Spain 1    |    |
|      |       |   | PC437             |    |
|      |       |   | PC850             |    |
|      |       |   | PC858             |    |
|      |       |   | PC852             |    |
|      |       |   | PC853             |    |
|      |       |   | PC855             |    |
|      |       |   | PC857             |    |
|      |       |   | PC866             |    |
|      |       |   | PC869             |    |
|      |       |   | PC437 Greek       |    |
|      |       |   | ISO Latin 1T      |    |
|      |       |   | ISO 8859-7        |    |
|      |       |   | Code MJK          |    |
|      |       |   | MAZOWIA           |    |
|      |       |   | Bulgaria          |    |

| Font | Pause |   |                    |    |
|------|-------|---|--------------------|----|
| 1    | 2     | 3 |                    |    |
|      |       |   | “ Auto line feed ” | .G |
|      |       |   | Off                |    |
|      |       |   | On                 |    |

| Font | Pause |   |                |         |
|------|-------|---|----------------|---------|
| 1    | 2     | 3 |                |         |
|      |       |   | “Page length ” | .H      |
|      |       |   | 11 inch        |         |
|      |       |   | 12 inch        | 14 inch |
|      |       |   | 8.5 inch       | 8 inch  |
|      |       |   | 70/6 inch (A4) | 6 inch  |
|      |       |   | 5.5 inch       | 4 inch  |

7 inch 3.5 inch  
17 inch 3 inch

| Font | Pause |   |                      |
|------|-------|---|----------------------|
| 1    | 2     | 3 |                      |
|      |       |   | “ Auto tear Off ” .I |
|      |       |   | Off                  |
|      |       |   | On                   |

| Font | Pause |   |               |
|------|-------|---|---------------|
| 1    | 2     | 3 |               |
|      |       |   | “Tractor ” .J |
|      |       |   | Single        |
|      |       |   | Double        |

| Font | Pause |   |                         |
|------|-------|---|-------------------------|
| 1    | 2     | 3 |                         |
|      |       |   | “Interface” .K          |
|      |       |   | Auto selection (10sec.) |
|      |       |   | Auto selection (30sec.) |
|      |       |   | Parallel                |
|      |       |   | Serial                  |

| Font | Pause |   |               |
|------|-------|---|---------------|
| 1    | 2     | 3 |               |
|      |       |   | “Bit rate” .L |
|      |       |   | 300BPS        |
|      |       |   | 600BPS        |
|      |       |   | 1200BPS       |
|      |       |   | 2400BPS       |
|      |       |   | 4800BPS       |
|      |       |   | 9600BPS       |
|      |       |   | 19200BPS      |

| Font | Pause |   |             |
|------|-------|---|-------------|
| 1    | 2     | 3 |             |
|      |       |   | “Parity” .M |
|      |       |   | None        |
|      |       |   | Odd         |
|      |       |   | Even        |

| Font | Pause |   |                  |
|------|-------|---|------------------|
| 1    | 2     | 3 |                  |
|      |       |   | “Data length” .N |
|      |       |   | 7 bit            |
|      |       |   | 8 bit            |

| Font | Pause |   |                |
|------|-------|---|----------------|
| 1    | 2     | 3 |                |
|      |       |   | “ ETX/ACK ” .O |
|      |       |   | Off            |
|      |       |   | On             |

| Font |   | Pause |  |            |    |
|------|---|-------|--|------------|----|
| 1    | 2 | 3     |  |            |    |
|      |   |       |  | “Software” | .P |
|      |   |       |  | ESC/P      |    |
|      |   |       |  | IBM 2380   |    |

| Font |   | Pause |  |           |    |
|------|---|-------|--|-----------|----|
| 1    | 2 | 3     |  |           |    |
|      |   |       |  | “Auto CR” | .Q |
|      |   |       |  | Off       |    |
|      |   |       |  | On        |    |

|  |  |  |  |           |  |          |       |
|--|--|--|--|-----------|--|----------|-------|
|  |  |  |  | “Pause”,  |  |          |       |
|  |  |  |  | “LF/FF”   |  |          |       |
|  |  |  |  | ,         |  | “Pause”, | LF/FF |
|  |  |  |  |           |  |          | ( ÷Q) |
|  |  |  |  | “Parity”. |  |          |       |
|  |  |  |  | ,         |  |          |       |

. .2.3-2.5.

.1 ,

-22/

OE-V(P)T.